

## ZUMINOL SOLUTION

### ZUMINOL SOLUTION ATF 6HP

SOLUTION ATF 6HP is a synthetic automatic transmission oil, which has been especially developed for automatic gear boxes requiring low viscosity ATF. SOLUTION ATF 6HP ensures easy shifting under all operating temperatures, without unnecessary friction. Because of the low pour point and the high VI, SOLUTION ATF 6HP can be applied in a wide temperature range. Because of the excellent oxidation and thermal stability, SOLUTION ATF 6HP keeps its unique properties, so it easily meets the prescribed drain intervals. A unique combination of synthetic base oils and state-of-the-art additives, guarantee all-round, easy shifting. The low viscosity ensures a fuel economy benefit compared to conventional viscosity ATF.

#### SPECIFICATION LEVEL OR PERFORMANCE

- AML 4G4319A509/AA/S
- BENTLEY PY112995PA
- BMW 83220142516
- M-1375-4
- HYUNDAI 040000C90SG
- JAGUAR Fluid 8432
- LAND ROVER TYK500050
- MASERATI 231603
- VW G 055 005
- ZF TE-ML 11

#### TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15 °C	kg/l	0.845
Viscosity 40 °C	mm <sup>2</sup> /s	31.0
Viscosity 100 °C	mm <sup>2</sup> /s	6.0
Viscosity Index		153
Flash Point COC	°C	210
Brookfield viscosity at -40 °C	mPas	9500
Color		AMBER

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*