

ZUMINOL SOLUTION

ZUMINOL SOLUTION ATF CVT PLUS

Zuminol Solution ATF CVT Plus is a full synthetic lubricant and has been designed to be used in most CVT gearboxes. It is suitable for continuously variable transmissions, using steel push-belts or chains. It offers outstanding anti-wear protection and stable friction characteristics.

SPECIFICATION LEVEL OR PERFORMANCE

- MB 236.20
- AUDI TL 52 180 (G052 180)
- BMW 83220136376 / 83220429159
- MINI (EZL799)
- DODGE/JEEP NS-2/CVTF+4
- GM/SATURN DEX-CVT
- HONDA HCF-II/HMMF
- HYUNDAI SP-CVT1/SP-III
- MITSUBISHI CVTF-J1/SP-III
- NISSAN NS-I/II/III
- TOYOTA TC SUBARU
- LINEARTRONIC CVTF/TC/NS-2/CVT GREEN 1
- SUZUKI TC/NS-2/CVT GREEN1
- DAIHATSU AMMIX CVT

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15 °C	g/ml	0.848
Viscosity 40 °C	mm ² /s	35.4
Viscosity 100 °C	mm ² /s	7.3
Viscosity Index		177
Flash Point COC	°C	214
Pour Point °C	cP	-48
Total Base Number	mgKOH/g	3.6

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.