

ZUMINOL SOLUTION

ZUMINOL SOLUTION ATF CVT

Zuminol Solution ATF CVT is a full synthetic continuously variable transmission fluid. It offers excellent thermal and oxidative stability, low-temperature fluidity, shear stability, and high wear protection.

SPECIFICATION LEVEL OR PERFORMANCE

- Toyota T,T-II,T-III,T-IV, WS
- Nissan Matic Fluid C, D, J
- Honda Ultra II, Ultra Z-1, Ultra HMMF
- Mitsubishi SP-II, SP-III, ATF-II, ATF-SK, SP-IV
- Suzuki ATF Oil, ATF Oil Special
- Subaru ATF
- Kia
- Isuzu Besco ATF II, III
- Daihatsu Alumix ATF Multi
- Mercon
- Allison C-4
- JWS 3309, 3317
- JASO M 315 Type 1A
- BMW 7045E
- Chrysler ATF, ATF +3, ATF +4
- VW/AUDI G-055-025-AZ

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15 °C	g/ml	0.846
Viscosity 40 °C	mm ² /s	36.6
Viscosity 100 °C	mm ² /s	7.2
Viscosity Index		165
Flash Point COC	°C	212
Pour Point °C	cP	-48
Total Base Number	mgKOH/g	2.7

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.