

ZUMINOL SOLUTION

ZUMINOL SOLUTION ATF IV

SOLUTION ATF IV is high performance full synthetic transmission oil for automatic transmissions, power steering and hydraulic systems in passenger cars and trucks.

SPECIFICATION LEVEL OR PERFORMANCE

- FORD MERCON V
- GM DEXRON III-H
- AISIN-WARNER JWS 3309
- TOYOTA TYPE-III / IV
- VW G 055 025
- ALLISON TES 295
- MB 236.11/ 236.3 / 236.7/ 236.10
- VW G 052 025 / 052 055 / 052 162 / 052 533/ 052 990
- BMW LT 71141
- HYUNDAI SP-III
- HONDA ATF Z-1
- NISSAN MATIC-J / K/ W
- AISIN-WARN ER JWS 3314 / 3317

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15 °C	g/ml	0.861
Viscosity 40 °C	mm ² /s	35.6
Viscosity 100 °C	mm ² /s	8.1
Viscosity Index		212
Flash Point COC	°C	178
Viscosity -40 °C	cP	12.000
Color		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.