

ZUMINOL SOLUTION

PRO 5W40 FULLY SYNTHETIC MOTOR OIL

CONTAINS PAO

ZUMINOL SOLUTION PRO 5W-40 is a fully synthetic lubricant based on carefully selected very high quality base oils. It is formulated with excellent additives to meet the demanding requirements of the VW 505.01 specification in terms of resistance to oxidation, oil thickening and the formation of sludge in the engine.

ZUMINOL SOLUTION PRO 5W-40 is a Mid SAPS oil (sulfated ash, phosphorus and sulfur content), which corresponds to Euro 4 and Euro 5 norms. It provides reliable protection of after-treatment devices and Diesel Particulate Filters. The oil is very universal in use and can be used for petrol and diesel engines.

SPECIFICATION LEVEL OR PERFORMANCE

- API SN/CF
- ACEA C3, A3/B4
- MB: 229.51/229.31
- VW 502.00/505.01
- Porsche
- BMW LL-04

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15°C	kg/l	0,850
Viscosity at -30°C	mPas	5500
Viscosity at 40°C	mm ² /s	82,80
Viscosity at 100°C	mm ² /s	14,00
Viscosity Index		175
Flash Point COC	°C	232
Pour Point	°C	-42
Total Base Number	mgKOH/g	7,4
Sulphate Ash	%	0,77

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.