

ZUMINOL PROCHAMP MARIEKATE

0W20 C6 FULLY SYNTHETIC MOTOR OIL

High performance full synthetic "Mid Saps" motor oil, suitable for gasoline, LPG or diesel engines with or without turbo, where the above specifications are required. The state-of-the-art additive package helps to offer effective mitigation of LSPI. Avoid used oil contact with the skin. In case that contact occurs, rinse with water and soap. Dispose of used oil in accordance with local laws. Safety data sheet available for professional user on request.

SPECIFICATIONS

- ACEA C5/C6
- API SQ, SP
- VW 508 00 / 509 00
- MB 229.71 / 229.72
- BMW Longlife 17FE
- VOLVO VCC RBSO-2AE
- Porsche C20
- Ford WSS-M2C947-A1 / 956-A1 / 962-A1
- GM Dexos D
- Opel OV0401547
- ST JLR 03.5006

PACKAGING

1L can (12 x 1L carton), 4L can, 20L can, 200L can, 208L can

TYPICAL CHARACTERISTICS

Test Items	Unit	Average Value
Density at 15°C	g/mL	0.8449
Viscosity 40°C	mm ² /s	40.89
Viscosity 100°C	mm ² /s	7.995
Viscosity -35°C	mPaS	5210
Viscosity index	°C	172
Flash point COC	°C	222
Pour point	°C	-39
Total base number	mgKOH/g	8.8
Sulphated ash content	%wt	0.76

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.