

ZUMINOL PROCHAMP MARIEKATE

5W30 C3 FULLY SYNTHETIC MOTOR OIL

High performance full synthetic "Mid Saps" motor oil, suitable for gasoline, LPG or diesel engines with or without turbo, where the above specifications are required. The state-of-the-art additive package helps to offer effective mitigation of LSPI. Avoid used oil contact with the skin. In case that contact occurs, rinse with water and soap. Dispose of used oil in accordance with local laws. Safety data sheet available for professional user on request.

SPECIFICATIONS

- API SQ, API SP
- ACEA C3
- VW 504 00/507 00
- MB 229.52
- BMW Longlife-04
- Porsche C30
- RENAULT-RN17 LEVEL
- FORD WSS-M2C917-A

PACKAGING

1L can (12 x 1L carton), 4L can, 20L can, 200L can, 208L can

TYPICAL CHARACTERISTICS

Test Items	Unit	Average Value
Density at 20°C	g/mL	0.85098
Viscosity 40°C	mm ² /s	74.91
Viscosity 100°C	mm ² /s	7.995
Viscosity index	°C	163
TBN mg	KOH/g	9.68
Flash point COC	°C	230
Pour point	°C	-39
CCS@ -30°C	cP	6202

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.